

MTX Zerex - Holders

Clear Zero-Halogen
transparent profile carrier

TECHNICAL DATA SHEET

Revision Number. 1
Last Edited 5. januar 2024



The MTX Zerex holders are zero-halogen carriers, profiled to allow each type to accommodate a range of cable sizes. Select the holder size based on the actual external diameter of the wire or cable due to variations in the insulation thickness and conductor format. The MTX profile allows quick mounting and easy adjustment on the wire.

To be used in conjunction with MTX push in markers. No tools needed.

Kabel diameter from 0,5mm to 26mm or 0,5mm² to 240mm²

UV STABILITY DATA.

Results of accelerated ageing testing are as a result of artificial lighting/ illumination in a laboratory. Duration test is 500 hours, which equals 10 years of exposure.

Industry



Industry



Marine



Wind power



Commercial



Aerospace



Construction



Railway



Military



Electrical installations



Petrochemical



Telecom

STANDARD COLORS



Clear

MATERIAL

Ethylen Vinyl acetate. co-polymer compound - Lead Free

OPERATING TEMPERATURE

-40°C up to +90°C
(-40F to 194°F)

PROCESSING METHOD

Extruded profile

RESISTANCE TO SOLVENTS

Alkali - Alcohol - Acid -and many other solvent

ROHS COMPLIANT

Yes

FLAMMABILITY STANDARD

Class V-0 - UL94
Not flammable

HALOGEN FREE

Yes

THERMAL RESISTANCE

CEI 16-7 The material is compliant to CEI 17-7

UV STABILITY TEST

The markers has been tested for 500 hours and passed the test to be compliant to UNI EN ISO 4892-2 standard

STORAGE

Cool and dry in original packaging. Recommended temperature at +10°C to +25°C and 45-55% relative humidity.

APPLICATIONS

Developed to be used in normal Industry, Wind Power, Commercial, Construction, Electrical and Telecom installations, wire & cable bundling.

Ordering Info

PART NUMBER	TYPE	KABEL DIAMETER	MATERIAL	QTY	Section range	UOM	Holder Length	
MTXC-015-00-ZE	Carrier	1,3-2,2mm	Clear PVC	2000	0,25-0,5mm ²	Box	15mm	
MTXC-015-01-ZE	Carrier	2,0-3,7 mm	Clear PVC	1000	0,5-2,5mm ²	Box	15mm	
MTXC-015-02-ZE	Carrier	3,5-10,0 mm	Clear PVC	1000	2,5-4.0mm ²	Box	15mm	
MTXC-015-03-ZE	Carrier	8,0-16,0 mm.	Clear PVC	500	4.0-10.0mm ²	Box	15mm	

PART NUMBER	TYPE	KABEL DIAMETER	MATERIAL	QTY	Section range	UOM	Holder Length	
MTXC-030-00-ZE	Carrier	1,3-2,2mm	Clear PVC	2000	0,25-0,5mm ²	Box	30mm	
MTXC-030-01-ZE	Carrier	2,0-3,7 mm	Clear PVC	1000	0,5-2,5mm ²	Box	30mm	
MTXC-030-02-ZE	Carrier	3,5-10,0 mm	Clear PVC	1000	2,5-4.0mm ²	Box	30mm	
MTXC-030-03-ZE	Carrier	8,0-16,0 mm.	Clear PVC	500	4.0-10.0mm ²	Box	30mm	

General Values for Zero-Halogen PVC Compound

PHYSICAL

PROPERTIES	TEST METHOD	TYPICAL VALUE
Density Stress (gram/cm ³)	ISO 1183	1,27 g/cm ³
Hardness to 15"- Shore A	ISO 686	83
Vicat softening point 5Kg	ISO 527	83,5 °C
Tensile Strength	ISO 527	19N/mm ²

THERMAL

PROPERTIES	TEST METHOD	TYPICAL VALUE
Melting Point	88°C 189°F

ENVIRONMENTAL

PROPERTIES	TEST METHOD	TYPICAL VALUE
TEST with XENON lamp, XENON (340nm) - Light 65 ° c irradiation 0.50 W/m ² duration 1,42 hours - Light + Spray duration 0.60 W/m ² duration 18 min	Visual Inspection	No creasing or cracking

